

- power: 10 W
 - length: 873 mm
 - luminous flux: 1 060 lm
 - color temperature: 4 000 K
 - light color: neutral white
 - material: aluminium (Al) + plastic
 - dimensions: 873 × 22 × 30 mm
 - lifetime: 25 000 hours
 - beam angle: 120°
- packaging: 1 pc, small box
 - energy efficiency class: A+



ZS2131
15 43 213 100

1/-/-/20
ZS2131


- power: 14 W
 - length: 1 173 mm
 - luminous flux: 1 300 lm
 - color temperature: 4 000 K
 - light color: neutral white
 - material: aluminium (Al) + plastic
 - dimensions: 1 173 × 22 × 30 mm
 - lifetime: 25 000 hours
 - beam angle: 120°
- packaging: 1 pc, small box
 - energy efficiency class: A+



ZS2141
15 43 214 100

1/-/-/20
ZS2141

- power: 5 W
 - length: 300 mm
 - luminous flux: 500 lm
 - color temperature: 4 000 K
 - light color: neutral white
 - material: aluminium (Al) + plastic
 - dimensions: 300 × 23 × 37 mm
 - lifetime: 25 000 hours
 - beam angle: 120°
- packaging: 1 pc, small box



ZS2110
15 31 211 010

1/-/-/30
ZS2110

- power: 10 W
 - length: 600 mm
 - luminous flux: 1 000 lm
 - color temperature: 4 000 K
 - light color: neutral white
 - material: aluminium (Al) + plastic
 - dimensions: 600 × 23 × 37 mm
 - lifetime: 25 000 hours
 - beam angle: 120°
- packaging: 1 pc, small box
 - energy efficiency class: A+



ZS2120
15 31 211 020

1/-/-/30
ZS2120

- power: 15 W
 - length: 860 mm
 - luminous flux: 1 400 lm
 - color temperature: 4 000 K
 - light color: neutral white
 - material: aluminium (Al) + plastic
 - dimensions: 860 × 23 × 37 mm
 - lifetime: 25 000 hours
 - beam angle: 120°
- packaging: 1 pc, small box
 - energy efficiency class: A+



ZS2130
15 31 211 030

1/-/-/30
ZS2130