



- power: 30 W
- luminous flux: 2 400 lm
- replacement of incandescent bulb: 260 W
- color temperature: 6 500 K
- light color: cool white
- color rendering index (CRI): Ra > 80
- voltage: 14.5 V DC 100-240 V AC
- IP rating: IP54
- beam angle: 120°

- dimensions: 295 × 225 × 135 mm
- battery: Li-Ion 4 400 mAh
- AKU lighting time: 2.5 - 10 hours
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZS2831 1/-/-3
15 31 281 031 ZS2831

- power: 36 W
- luminous flux: 2 400 lm
- replacement of incandescent bulb: 250 W
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra >70
- voltage: 220-240 V~
- IP rating: IP54
- beam angle: 120°

- dimensions: 320 × 258 × 83 mm
- supply cable length: 1.5 m
- number of adapter plugs: 1
- adapter plug type: FRENCH
- lead-in cable material: rubber
- lead-in cable type: H07RN-F
- body material: aluminium + plastic
- mechanical impact protection: IK10
- packaging: 1 pc, box



ZS3110 1/-/-6
15 31 311 010 ZS3110

- power: 2× 20 W
- luminous flux: 2× 1 600 lm
- replacement of incandescent bulb: 2× 170 W
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP65
- beam angle: 120°

- dimensions: 860 × 860 × 1 890 mm
- supply cable length: 3 m
- lead-in cable material: rubber
- lead-in cable type: H07RN-F
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZS2221.2 1/-/-2
15 31 222 120 ZS2221.2

- power: 80 W
- luminous flux: 8 000 lm
- replacement of incandescent bulb: 850 W
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra >70
- voltage: 220-240 V~
- IP rating: IP54
- beam angle: 120°

- dimensions: 342 × 295 × 112 mm
- supply cable length: 3 m
- number of adapter plugs: 2
- adapter plug type: FRENCH
- lead-in cable material: rubber
- lead-in cable type: H07RN-F
- body material: aluminium + plastic
- mechanical impact protection: IK10
- packaging: 1 pc, box



ZS3120 1/-/-4
15 31 311 020 ZS3120

- power: 2× 30 W
- luminous flux: 2× 2 400 lm
- replacement of incandescent bulb: 2× 260 W
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP65
- beam angle: 120°

- dimensions: 860 × 860 × 1 890 mm
- supply cable length: 3 m
- lead-in cable material: rubber
- lead-in cable type: H07RN-F
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZS2231.2 1/-/-2
15 31 223 120 ZS2231.2