



www.emos.eu

Order Code
Item Number

Packaging
Type

- power: 50 W
- luminous flux: 4 500 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP65
- beam angle: 110°
- dimensions: 183 × 28 × 145 mm


- supply cable length: 20 cm
- detection range of PIR Sensor: 8 m
- lead-in cable material: rubber
- lead-in cable type: H05RN-F
- body material: aluminum
- packaging: 1 pc, box



ZS2242 1/-/-/20
15 31 224 200 ZS2242

- power: 10,5 W
- luminous flux: 900 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP44
- beam angle: 110°
- dimensions: 108 × 49 × 166 mm

- supply cable length: 20 cm
- detection range of PIR Sensor: 8 m
- lead-in cable material: rubber
- lead-in cable type: H05RN-F
- body material: aluminum
- packaging: 1 pc, box



ZS2312 1/-/-/15
15 31 231 200 ZS2312

- power: 20,5 W
- luminous flux: 1 800 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP44
- beam angle: 110°
- dimensions: 108 × 49 × 166 mm


- supply cable length: 20 cm
- detection range of PIR Sensor: 8 m
- lead-in cable material: rubber
- lead-in cable type: H05RN-F
- body material: aluminum
- packaging: 1 pc, box



ZS2322 1/-/-/15
15 31 232 200 ZS2322

- power: 30 W
- luminous flux: 2 700 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP44
- beam angle: 110°
- dimensions: 143 × 51 × 190 mm

- supply cable length: 20 cm
- detection range of PIR Sensor: 8 m
- lead-in cable material: rubber
- lead-in cable type: H05RN-F
- body material: aluminum
- packaging: 1 pc, box



ZS2332 1/-/-/10
15 31 233 200 ZS2332

- power: 50 W
- luminous flux: 4 500 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP44
- beam angle: 110°
- dimensions: 183 × 51 × 218 mm

- supply cable length: 20 cm
- detection range of PIR Sensor: 8 m
- lead-in cable material: rubber
- lead-in cable type: H05RN-F
- body material: aluminum
- packaging: 1 pc, box



ZS2342 1/-/-/10
15 31 234 200 ZS2342