

## Luminaires

## LED, halogen floodlights

## PROFI PLUS

- SMD technology – PHILIPS LUMILEDS LED chips
- luminous efficacy of up to 130 lm/W
- light angle: 120° horizontally, 90° vertically
- Al body, rubber lead-in cable, IP65 – suitable for outdoors
- unique design, easy installation via mount
- diffuser material: plastic (PC)
- 5 year warranty

- power: 15 W
- luminous flux: 1 600 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 100–240 V
- IP rating: IP65
- beam angle: 120 × 90°
- dimensions: 108 × 82 × 37 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- lead-in cable type: H05RN-F
- body material: aluminum
- mechanical impact protection: IK10
- packaging: 1 pc, box

**ZS2410**

1/-/-/10

15 31 241 010

ZS2410

- power: 15 W
- luminous flux: 1 800 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 100–240 V
- IP rating: IP65
- beam angle: 120 × 90°
- dimensions: 112 × 85 × 45 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- lead-in cable type: H05RN-F
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box

**ZS2412**

1/-/-/10

15 31 241 200

ZS2412

- power: 30 W
- luminous flux: 3 500 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 100–240 V
- IP rating: IP65
- beam angle: 120 × 90°
- dimensions: 171 × 130 × 40 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- lead-in cable type: H05RN-F
- body material: aluminum
- mechanical impact protection: IK10
- packaging: 1 pc, box

**ZS2420**

1/-/-/10

15 31 241 020

ZS2420