



www.emos.eu

Order Code
Item Number

Packaging
Type

- power: 30 W
- luminous flux: 4 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 100-240 V
- IP rating: IP65
- beam angle: 120 × 90°
- dimensions: 173 × 130 × 50 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- lead-in cable type: H05RN-F
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZS2422
15 31 242 200

1/-/-10
ZS2422



- power: 50 W
- luminous flux: 5 600 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 100-240 V
- IP rating: IP65
- beam angle: 120 × 90°
- dimensions: 217 × 154 × 45 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- lead-in cable type: H05RN-F
- body material: aluminum
- mechanical impact protection: IK10
- packaging: 1 pc, box



ZS2430
15 31 241 030

1/-/-6
ZS2430



- power: 50 W
- luminous flux: 6 200 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 100-240 V
- IP rating: IP65
- beam angle: 120 × 90°
- dimensions: 221 × 156 × 52 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- lead-in cable type: H05RN-F
- body material: aluminum
- mechanical impact protection: IK10
- packaging: 1 pc, box



ZS2432
15 31 243 200

1/-/-6
ZS2432



- power: 100 W
- luminous flux: 12 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 100-240 V
- IP rating: IP65
- beam angle: 120 × 90°
- dimensions: 320 × 250 × 86 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- lead-in cable type: H05RN-F
- body material: aluminum
- mechanical impact protection: IK10
- packaging: 1 pc, box



ZS2450
15 31 241 050

1/-/-1
ZS2450



- power: 100 W
- luminous flux: 13 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 100-240 V
- IP rating: IP65
- beam angle: 120 × 90°
- dimensions: 320 × 280 × 85 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- lead-in cable type: H05RN-F
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZS2452
15 31 245 200

1/-/-1
ZS2452

