



www.emos.eu

Order Code
Item Number

Packaging
Type

- power: 150 W
- luminous flux: 20 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP65
- beam angle: 120 × 90°
- dimensions: 280 × 320 × 87 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- lead-in cable type: H05RN-F
- body material: aluminum
- mechanical impact protection: IK10
- packaging: 1 pc, box



ZS2460 1/-/-/1
15 31 241 060 ZS2460

- power: 150 W
- luminous flux: 19 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 100-240 V
- IP rating: IP65
- beam angle: 120 × 90°
- dimensions: 320 × 280 × 85 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- lead-in cable type: H05RN-F
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZS2462 1/-/-/1
15 31 246 200 ZS2462

- power: 230 W
- luminous flux: 30 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP65
- beam angle: 120 × 90°
- dimensions: 360 × 320 × 87 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- lead-in cable type: H05RN-F
- body material: aluminum
- mechanical impact protection: IK10
- packaging: 1 pc, box



ZS2470 1/-/-/1
15 31 241 070 ZS2470

- power: 300 W
- luminous flux: 40 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 100-240 V
- IP rating: IP65
- beam angle: 120 × 90°
- dimensions: 321 × 465 × 95 mm

- supply cable length: 1 m
- lead-in cable material: rubber
- lead-in cable type: H05RN-F
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZS2472 1/-/-/1
15 31 247 200 ZS2472