

TAMBO

- aluminium body with clean design
- PIR sensor detection angle: 120°
- luminous efficacy: 80 lm/W
- modern milky PC diffuser
- light angle: 120°
- angled mount for easier installation onto a wall
- 3 year warranty

- power: 10 W
- luminous flux: 800 lm
- replacement of incandescent bulb: 85 W
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP65
- beam angle: 120°

- dimensions: 105 × 102 × 70 mm
- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box

**ZS2511**

1/-/-14

15 31 242 511

ZS2511

- power: 20 W
- luminous flux: 1 600 lm
- replacement of incandescent bulb: 170 W
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP65
- beam angle: 120°

- dimensions: 135 × 102 × 70 mm
- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box

**ZS2521**

1/-/-12

15 31 242 521

ZS2521

- power: 30 W
- luminous flux: 2 400 lm
- replacement of incandescent bulb: 260 W
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP65
- beam angle: 120°

- dimensions: 116 × 114 × 70 mm
- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box

**ZS2531**

1/-/-10

15 31 242 531

ZS2531

- power: 50 W
- luminous flux: 4 000 lm
- replacement of incandescent bulb: 430 W
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP65
- beam angle: 120°

- dimensions: 210 × 142 × 70 mm
- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box

**ZS2541**

1/-/-7

15 31 242 541

ZS2541