

## ILIO

- aluminium body with unique slim design
- PIR sensor detection angle: 120°
- luminous efficacy: 80 lm/W
- modern milky PC diffuser
- light angle: 120°
- terminal board for connecting lead-in cable inside spotlight
- angled mount for easier installation onto a wall
- 3 year warranty

- power: 10 W
- luminous flux: 800 lm
- replacement of incandescent bulb: 85 W
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP65
- beam angle: 120°

- dimensions: 117 × 92 × 55 mm
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



**ZS2510** 1/-/-20  
15 31 252 510 ZS2510



- power: 20 W
- luminous flux: 1 600 lm
- replacement of incandescent bulb: 170 W
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP65
- beam angle: 120°

- dimensions: 150 × 108 × 55 mm
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



**ZS2520** 1/-/-20  
15 31 252 520 ZS2520



- power: 30 W
- luminous flux: 2 400 lm
- replacement of incandescent bulb: 260 W
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP65
- beam angle: 120°

- dimensions: 185 × 135 × 55 mm
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



**ZS2530** 1/-/-12  
15 31 252 530 ZS2530



- power: 50 W
- luminous flux: 4 000 lm
- replacement of incandescent bulb: 430 W
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP65
- beam angle: 120°

- dimensions: 215 × 155 × 55 mm
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



**ZS2540** 1/-/-10  
15 31 252 540 ZS2540

