



www.emos.eu

Order Code
Item Number

Packaging
Type

- power: 10 W
- luminous flux: 1 100 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP65
- beam angle: 120°
- dimensions: 95 × 70 × 27 mm

- supply cable length: 30 cm
- detection range of PIR Sensor: 10 m
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK06
- packaging: 1 pc, box



ZS2712 1/-/-/20
15 31 242 712 ZS2712

- power: 20 W
- luminous flux: 2 200 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP65
- beam angle: 120°
- dimensions: 135 × 95 × 28 mm

- supply cable length: 30 cm
- detection range of PIR Sensor: 10 m
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK06
- packaging: 1 pc, box



ZS2722 1/-/-/20
15 31 242 722 ZS2722

- power: 30 W
- luminous flux: 3 300 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP65
- beam angle: 120°
- dimensions: 160 × 110 × 28 mm

- supply cable length: 30 cm
- detection range of PIR Sensor: 10 m
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK06
- packaging: 1 pc, box



ZS2732 1/-/-/10
15 31 242 732 ZS2732

- power: 50 W
- luminous flux: 5 500 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP65
- beam angle: 120°
- dimensions: 200 × 145 × 28 mm

- supply cable length: 30 cm
- detection range of PIR Sensor: 10 m
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK06
- packaging: 1 pc, box



ZS2742 1/-/-/10
15 31 242 742 ZS2742