



www.emos.eu

Order Code
Item Number

Packaging
Type

- power: 20 W
- luminous flux: 2 000 lm
- color temperature: 6 500 K
- light color: cool white
- color rendering index (CRI): Ra > 80
- voltage: 5 V DC 220–240 V AC
- IP rating: IP54
- beam angle: 120°
- dimensions: 266 × 220 × 273 mm

- battery: Li-Ion 6 600 mAh
- AKU lighting time: 3 – 10 hours
- body material: aluminum
- packaging: 1 pc, box



| | | | | | | | |
|--|--|--|--|--|--|--|--|
| | | | | | | | |
|--|--|--|--|--|--|--|--|



ZS2822 1/-/-4
15 31 282 200 ZS2822

- power: 30 W
- luminous flux: 3 000 lm
- color temperature: 6 500 K
- light color: cool white
- color rendering index (CRI): Ra > 80
- voltage: 5 V DC 220–240 V AC
- IP rating: IP54
- beam angle: 120°
- dimensions: 292 × 219 × 273 mm

- battery: Li-Ion 10 000 mAh
- AKU lighting time: 3 – 10 hours
- body material: aluminum
- packaging: 1 pc, box



| | | | | | | | |
|--|--|--|--|--|--|--|--|
| | | | | | | | |
|--|--|--|--|--|--|--|--|



ZS2832 1/-/-2
15 31 283 200 ZS2832

- power: 10 W
- luminous flux: 800 lm
- color temperature: 6 500 K
- light color: cool white
- color rendering index (CRI): Ra > 80
- voltage: 12 V DC 100–240 V AC
- IP rating: IP54
- beam angle: 120°
- battery: Li-Ion 2 200 mAh

- AKU lighting time: 2.5 – 10 hours
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



| | | | | | | |
|--|--|--|--|--|--|--|
| | | | | | | |
|--|--|--|--|--|--|--|



ZS2811 1/-/-8
15 31 281 110 ZS2811

- power: 20 W
- luminous flux: 1 600 lm
- color temperature: 6 500 K
- light color: cool white
- color rendering index (CRI): Ra > 80
- voltage: 14.5 V DC 100–240 V AC
- IP rating: IP54
- beam angle: 120°
- battery: Li-Ion 4 400 mAh

- AKU lighting time: 2.5 – 10 hours
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



| | | | | | | |
|--|--|--|--|--|--|--|
| | | | | | | |
|--|--|--|--|--|--|--|



ZS2821 1/-/-3
15 31 281 021 ZS2821

- power: 30 W
- luminous flux: 2 400 lm
- color temperature: 6 500 K
- light color: cool white
- color rendering index (CRI): Ra > 80
- voltage: 14.5 V DC 100–240 V AC
- IP rating: IP54
- beam angle: 120°
- dimensions: 252 × 143 × 328 mm

- battery: Li-Ion 4 400 mAh
- AKU lighting time: 2.5 – 10 hours
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



| | | | | | | |
|--|--|--|--|--|--|--|
| | | | | | | |
|--|--|--|--|--|--|--|



ZS2831 1/-/-3
15 31 281 031 ZS2831