



- power: 10 W
- luminous flux: 800 lm
- replacement of incandescent bulb: 85 W
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP44
- beam angle: 120°

- dimensions: 117 × 150 × 57 mm
- body material: aluminum
- mechanical impact protection: IK06
- packaging: 1 pc, box



ZS2910 1/-/-18
15 31 252 910 ZS2910

- power: 20 W
- luminous flux: 1 600 lm
- replacement of incandescent bulb: 170 W
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP44
- beam angle: 120°

- dimensions: 150 × 166 × 57 mm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK06
- packaging: 1 pc, box



ZS2920 1/-/-12
15 31 252 920 ZS2920

- power: 30 W
- luminous flux: 2 400 lm
- replacement of incandescent bulb: 260 W
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP44
- beam angle: 120°

- dimensions: 185 × 193 × 57 mm
- body material: aluminum
- mechanical impact protection: IK06
- packaging: 1 pc, box



ZS2930 1/-/-10
15 31 252 930 ZS2930

- power: 50 W
- luminous flux: 4 000 lm
- replacement of incandescent bulb: 430 W
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP44
- beam angle: 120°

- dimensions: 215 × 213 × 57 mm
- body material: aluminum
- mechanical impact protection: IK06
- packaging: 1 pc, box



ZS2940 1/-/-5
15 31 252 940 ZS2940