



www.emos.eu

Order Code
Item Number

Packaging
Type

- power: 10 W
- luminous flux: 800 lm
- replacement of incandescent bulb: 85 W
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP54
- beam angle: 120°

- dimensions: 105 × 143 × 70 mm
- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK06
- packaging: 1 pc, box



ZS2911 1/-/-/14
15 31 242 911 ZS2911

- power: 20 W
- luminous flux: 1 600 lm
- replacement of incandescent bulb: 170 W
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP54
- beam angle: 120°

- dimensions: 135 × 165 × 70 mm
- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK06
- packaging: 1 pc, box



ZS2921 1/-/-/12
15 31 242 921 ZS2921

- power: 30 W
- luminous flux: 2 400 lm
- replacement of incandescent bulb: 260 W
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP54
- beam angle: 120°

- dimensions: 165 × 185 × 70 mm
- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK06
- packaging: 1 pc, box



ZS2931 1/-/-/10
15 31 242 931 ZS2931

- power: 50 W
- luminous flux: 4 000 lm
- replacement of incandescent bulb: 430 W
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP54
- beam angle: 120°

- dimensions: 210 × 217 × 70 mm
- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK06
- packaging: 1 pc, box



ZS2941 1/-/-/7
15 31 242 941 ZS2941