

Luminaires

Work Lights

CLASSIC

ILIO

- portable LED floodlights for connection to the mains
- folding stand for easier transport and storage
- resistant to impacts (IK10) and water IP44
- 150 cm lead-in rubber cable
- for indoor and outdoor use
- beam angle: 110°
- 3 year warranty

- power: 21 W
- luminous flux: 1 900 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220–240 V~
- IP rating: IP44
- beam angle: 110°
- dimensions: 215 × 185 × 250 mm



- supply cable length: 1.5 m
- lead-in cable material: rubber
- lead-in cable type: H07RN-F
- body material: aluminum
- mechanical impact protection: IK10
- packaging: 1 pc, box

**ZS3322**

1/-/-/6

15 42 033 220

ZS3322

- power: 31 W
- luminous flux: 2 800 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220–240 V~
- IP rating: IP44
- beam angle: 110°
- dimensions: 240 × 185 × 275 mm



- supply cable length: 1.5 m
- lead-in cable material: rubber
- lead-in cable type: H07RN-F
- body material: aluminum
- mechanical impact protection: IK10
- packaging: 1 pc, box

**ZS3332**

1/-/-/4

15 42 033 320

ZS3332

- power: 51 W
- luminous flux: 4 600 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220–240 V~
- IP rating: IP44
- beam angle: 110°
- dimensions: 270 × 185 × 275 mm



- supply cable length: 1.5 m
- lead-in cable material: rubber
- lead-in cable type: H07RN-F
- body material: aluminum
- mechanical impact protection: IK10
- packaging: 1 pc, box

**ZS3342**

1/-/-/4

15 42 033 420

ZS3342