

Luminaires

Industrial luminaires

Dustproof

- modern, efficient replacement for fluorescent light fittings
- with high luminous efficacy (up to 145 lm/W) and long lifetime
- light up immediately to 100 %, in neutral or cool white
- ideal for lighting warehouses, halls, garages, corridors
- option for passthrough connection, stainless clips
- high enclosure rating IP66
- extended warranty for 5 years

- dimensions: 1 220 × 85 × 80 mm
- power: 36 W
- luminous flux: 5 200 lm
- color temperature: 4 000 K
- color rendering index (CRI): Ra >80
- beam angle: 120°
- IP rating: IP66
- through-wiring
- working temperature range: -20 °C to +35 °C

- clip material: stainless steel
- voltage: 220–240 V
- protection class: I
- packaging: 1 pc, box

**ZT1520**

1/-/-/9

15 46 136 300

ZT1520

- dimensions: 1 220 × 85 × 80 mm
- power: 36 W
- luminous flux: 5 200 lm
- color temperature: 4 000 K
- color rendering index (CRI): Ra >80
- beam angle: 120°
- IP rating: IP66
- through-wiring
- working temperature range: -20 °C to +35 °C

- dimming function: yes
- clip material: stainless steel
- voltage: 220–240 V
- protection class: I
- packaging: 1 pc, box

**ZT1520D**

1/-/-/9

15 46 136 301

ZT1520D

- dimensions: 1 220 × 85 × 80 mm
- power: 40 W
- luminous flux: 5 200 lm
- color temperature: 4 000 K
- color rendering index (CRI): Ra >80
- beam angle: 120°
- IP rating: IP66
- through-wiring
- working temperature range: -20 °C to +35 °C

- clip material: stainless steel
- voltage: 220–240 V
- protection class: I
- lumen output in emergency mode: 630 lm
- backup time: 3 hours
- battery warranty: 2 years
- packaging: 1 pc, box

**ZT1520E**

1/-/-/9

15 46 136 302

ZT1520E