



- dimensions: 754 × 53 × 35 mm
- power: 18 W
- luminous flux: 1 700 lm
- color temperature: 4 000 K
- color rendering index (CRI): Ra >80
- beam angle: 120°
- IP rating: IP65
- through-wiring
- working temperature range: -15 °C to +35 °C

- material: plastic (PC)
- clip material: no clips
- voltage: 220–240 V
- protection class: II
- packaging: 1 pc, blister



**ZT3020** 1/-/-/20  
15 46 135 700 ZT3020

- dimensions: 1 284 × 53 × 35 mm
- power: 36 W
- luminous flux: 3 600 lm
- color temperature: 4 000 K
- color rendering index (CRI): Ra >80
- beam angle: 120°
- IP rating: IP65
- through-wiring
- working temperature range: -15 °C to +35 °C

- material: plastic (PC)
- clip material: no clips
- voltage: 220–240 V
- protection class: II
- packaging: 1 pc, blister



**ZT3120** 1/-/-/20  
15 46 135 800 ZT3120

- dimensions: 1 564 × 53 × 35 mm
- power: 45 W
- luminous flux: 4 500 lm
- color temperature: 4 000 K
- color rendering index (CRI): Ra >80
- beam angle: 120°
- IP rating: IP65
- through-wiring
- working temperature range: -20 °C to +35 °C

- material: plastic (PC)
- clip material: no clips
- voltage: 220–240 V
- protection class: II
- packaging: 1 pc, blister



**ZT3220** 1/-/-/20  
15 46 135 900 ZT3220

- dimensions: 638 × 68 × 56 mm
- power: 18 W
- luminous flux: 1 700 lm
- color temperature: 4 000 K
- color rendering index (CRI): Ra >80
- beam angle: 120°
- IP rating: IP65
- through-wiring
- working temperature range: -20 °C to +35 °C

- material: plastic (PC)
- clip material: no clips
- voltage: 220–240 V
- protection class: II
- packaging: 1 pc, box



**ZT4020** 1/-/-/15  
15 46 136 000 ZT4020

- dimensions: 1 238 × 68 × 56 mm
- power: 36 W
- luminous flux: 3 600 lm
- color temperature: 4 000 K
- color rendering index (CRI): Ra >80
- beam angle: 120°
- IP rating: IP65
- through-wiring
- working temperature range: -20 °C to +35 °C

- material: plastic (PC)
- clip material: stainless steel
- voltage: 220–240 V
- protection class: II
- packaging: 1 pc, box



**ZT4120** 1/-/-/12  
15 46 136 100 ZT4120