



www.emos.eu

Order Code
Item Number

Packaging
Type

- dimensions: 1 538 × 68 × 56 mm
- power: 55 W
- luminous flux: 5 500 lm
- color temperature: 4 000 K
- color rendering index (CRI): Ra >80
- beam angle: 120°
- IP rating: IP65
- through-wiring
- working temperature range: -20 °C to +40 °C
- material: plastic (PC)
- clip material: no clips
- voltage: 220–240 V
- protection class: II
- packaging: 1 pc, box



ZT4220 1/-/-/9
15 46 136 200 ZT4220

HIGHBAYS

- industrial hanging lights with Osram LED chips
- with high luminous efficacy (170 lm/W) and long service life
- wide range of beam angles: 60°, 90° or 120°
- dimmable driver, energy class A++
- ideal for halls with high ceilings (shop floors, etc.)
- extended warranty for 5 years

- power: 100 W
- luminous flux: 17 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220–240 V~
- IP rating: IP65
- beam angle: 120°
- dimensions: 235 × 163 mm in diameter
- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZU210.12 1/-/-/1
15 46 136 700 ZU210.12

- power: 100 W
- luminous flux: 17 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220–240 V~
- IP rating: IP65
- beam angle: 90°
- dimensions: 235 × 163 mm in diameter
- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZU210.9 1/-/-/1
15 46 136 800 ZU210.9

- power: 100 W
- luminous flux: 17 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220–240 V~
- IP rating: IP65
- beam angle: 60°
- dimensions: 235 × 163 mm in diameter
- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZU210.6 1/-/-/1
15 46 136 900 ZU210.6