



www.emos.eu

Order Code
Item Number

Packaging
Type

- power: 150 W
- luminous flux: 25 500 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP65
- beam angle: 120°
- dimensions: 300 × 173 mm in diameter

- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZU215.12 1/-/-1
15 46 137 000 ZU215.12

- power: 150 W
- luminous flux: 25 500 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP65
- beam angle: 90°
- dimensions: 300 × 173 mm in diameter

- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZU215.9 1/-/-1
15 46 137 100 ZU215.9

- power: 150 W
- luminous flux: 25 500 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP65
- beam angle: 60°
- dimensions: 300 × 173 mm in diameter

- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZU215.6 1/-/-1
15 46 137 200 ZU215.6

- power: 200 W
- luminous flux: 34 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP65
- beam angle: 120°
- dimensions: 340 × 191 mm in diameter

- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZU220.12 1/-/-1
15 46 137 300 ZU220.12

- power: 200 W
- luminous flux: 34 000 lm
- color temperature: 4 000 K
- light color: neutral white
- color rendering index (CRI): Ra > 80
- voltage: 220-240 V~
- IP rating: IP65
- beam angle: 90°
- dimensions: 340 × 191 mm in diameter

- supply cable length: 30 cm
- lead-in cable material: rubber
- body material: aluminum
- mechanical impact protection: IK08
- packaging: 1 pc, box



ZU220.9 1/-/-1
15 46 137 400 ZU220.9