

Info generali

Interno - Lampade da parete

Indoor wall mounted adjustable lamp with multiple sources, in-built switch and diffuse and direct light emission



Ean	8021696035949
Articolo	HOTEL AP2 BIANCO
Installazione	Lampade da parete
Garanzia	5 years
Peso lordo	2.02 kg
Volume	0.016576 m ³

Info tecniche e installative

Peso netto	1.41 kg
Classe di isolamento	I
Grado di protezione	IP20
Conformità	CE
Temperatura d'esercizio	0° ~ +40 °C
Efficienza a pieno carico	X
Dimmer	NO, On-Off
Alimentazione	100-240 V AC 50/60 Hz Integrated switch button
Alimentatore	In-built, included Replaceable (by qualified operators only), electronic
Orientabilità	YES

Info sorgente e prestazionali

Sorgente integrata	Light bulb (not included), Integrated LED module
Sorgente sostituibile	Replaceable (LED: by qualified operators only)
Potenza	E27/LED max 1 x 60W / 1.5 W
Emissione	Diffuse + Direct
Consumo massimo	max 60W / LED 1.5 W
Caratteristiche LED	LED SMD BRIDGELUX
CCT LED	3000 K
Durata LED (t. 25°c)	20000 h
CRI	> 80
Fascio luminoso	23°
Flusso sorgente	55 lm
Flusso utile	LED 45 lm
Rischio fotobiologico	2
Lampadina inclusa	1 - E14 OLIVA 4W 3000K CRI80 SATIN