

Info generali

Interno - Lampade da parete


Indoor wall mounted adjustable linear fitting with integrated LED sources, in-built switch and direct light emission



Ean	8021696121130
Articolo	BOW AP D76 OTTONE
Installazione	Lampade da parete
Garanzia	5 years
Peso lordo	1.12 kg
Volume	0.032832 m ³

Info tecniche e installative

Peso netto	0.86 kg
Classe di isolamento	I
Grado di protezione	IP20
Conformità	CE
Temperatura d'esercizio	0° ~ +40 °C
Efficienza a pieno carico	X
Dimmer	NO, On-Off
Alimentazione	220-240 V AC 50/60 Hz Integrated switch button
Alimentatore	In-built, included Replaceable (by qualified operators only), electronic



Info sorgente e prestazionali

Sorgente integrata	Integrated LED module
Sorgente sostituibile	Replaceable (by qualified operators only)
Potenza	LED 8 W
Emissione	Direct
Consumo massimo	max 8,00 W
Caratteristiche LED	LED SMD
CCT LED	3000 K
Durata LED (t. 25°c)	20000 h
CRI	> 80
Fascio luminoso	110°
Flusso sorgente	980 lm
Flusso utile	660 lm
Lampadina inclusa	1 - E14 OLIVA 4W 3000K CRI80 SATIN