

Info generali

Tecnico - Sistemi

Indoor suspended, recessed or ceiling mounted linear fitting with integrated LED sources and direct light emission

Ean	8021696192499
Articolo	FLUO ACCENT 1800 3000K WH
Installazione	Sistemi
Garanzia	5 years
Peso lordo	6.63 kg
Volume	0.025675 m ³

Info tecniche e installative

Peso netto	3.86 kg
Classe di isolamento	I
Grado di protezione	IP20
Conformità	CE
Temperatura d'esercizio	0° ~ +40 °C
Efficienza a pieno carico	X
Dimmer	NO, On-Off
Alimentazione	220-240 V AC 50/60 Hz
Alimentatore	In-built, included Replaceable (by qualified operators only), electronic, tridonic
Accessori non inclusi	Mounting kit (suspension, recessed, surface), Dimmable driver, Blinded corner, Structure connector

Info sorgente e prestazionali

Sorgente integrata	Integrated LED module
Sorgente sostituibile	Replaceable (by qualified operators only)
Potenza	30 W
Emissione	Direct
Consumo massimo	max 30,00 W
Caratteristiche LED	LED SMD OSRAM
CCT LED	3000 K
Durata LED (t. 25°c)	50000 h
CRI	> 80
SDCM	3
Fascio luminoso	30°
UGR massimo	< 13
Flusso sorgente	2750 lm
Flusso utile	2200 lm

