



Info generali

Interno - Lampade da soffitto

Indoor ceiling mounted projector with integrated LED sources and direct light emission

Ean	8021696205991
Articolo	NITRO PL ROUND D08 BIANCO
Installazione	Lampade da soffitto
Garanzia	5 years
Peso lordo	0.44 kg
Volume	0.00125 m ³

Info tecniche e installative

Peso netto	0.39 kg
Classe di isolamento	II
Grado di protezione	IP20
Conformità	CE
Temperatura d'esercizio	0° ~ +40 °C
Efficienza a pieno carico	X
Dimmer	NO, On-Off
Alimentazione	220-240 V AC 50/60 Hz
Alimentatore	In-built, included Replaceable (by qualified operators only), electronic

Info sorgente e prestazionali

Sorgente integrata	Integrated LED module
Sorgente sostituibile	Replaceable (by qualified operators only)
Potenza	LED 10 W
Emissione	Direct
Consumo massimo	max 10,00 W
Caratteristiche LED	LED COB BRIDGELUX
CCT LED	3000 K
Durata LED (t. 25°c)	50000 h
CRI	> 90
Fascio luminoso	28°
Flusso sorgente	1100 lm
Flusso utile	950 lm
Rischio fotobiologico	2
Lampadina inclusa	1 - E14 OLIVA 4W 3000K CRI80 SATIN