

**Info generali****Interno - Lampade da soffitto**


Indoor ceiling mounted lamp with integrated LED sources and direct light emission



|                      |                                           |
|----------------------|-------------------------------------------|
| <b>Ean</b>           | 8021696265971                             |
| <b>Articolo</b>      | ORACLE SLIM PL D050 ROUND 3000K ON-OFF WH |
| <b>Installazione</b> | Lampade da soffitto                       |
| <b>Garanzia</b>      | 5 years                                   |
| <b>Peso lordo</b>    | 2.19 kg                                   |
| <b>Volume</b>        | 0.045486 m <sup>3</sup>                   |

**Info tecniche e installative**

|                                  |                                                                                |
|----------------------------------|--------------------------------------------------------------------------------|
| <b>Peso netto</b>                | 1.24 kg                                                                        |
| <b>Classe di isolamento</b>      | II                                                                             |
| <b>Grado di protezione</b>       | IP20                                                                           |
| <b>Conformità</b>                | CE                                                                             |
| <b>Temperatura d'esercizio</b>   | 0° ~ +40 °C                                                                    |
| <b>Efficienza a pieno carico</b> | X                                                                              |
| <b>Dimmer</b>                    | NO, On-Off                                                                     |
| <b>Alimentazione</b>             | 220-240 V AC 50/60 Hz                                                          |
| <b>Alimentatore</b>              | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

**Info sorgente e prestazionali**

|                              |                                           |
|------------------------------|-------------------------------------------|
| <b>Sorgente integrata</b>    | Integrated LED module                     |
| <b>Sorgente sostituibile</b> | Replaceable (by qualified operators only) |
| <b>Potenza</b>               | LED 32 W                                  |
| <b>Emissione</b>             | Direct                                    |
| <b>Consumo massimo</b>       | max 32,00 W                               |
| <b>Caratteristiche LED</b>   | LED SMD                                   |
| <b>CCT LED</b>               | 3000 K                                    |
| <b>Durata LED (t. 25°c)</b>  | 20000 h                                   |
| <b>CRI</b>                   | > 80                                      |
| <b>SDCM</b>                  | 3                                         |
| <b>Fascio luminoso</b>       | 115°                                      |
| <b>Flusso sorgente</b>       | 3150 lm                                   |
| <b>Flusso utile</b>          | 1870 lm                                   |
| <b>Lampadina inclusa</b>     | 1 - E14 OLIVA 4W 3000K CRI80 SATIN        |