

## Info generali

## Interno - Lampade da parete

Indoor wall mounted linear fitting with integrated LED sources, enhanced protection and diffuse light emission

|                      |                        |
|----------------------|------------------------|
| <b>Ean</b>           | 8021696302232          |
| <b>Articolo</b>      | RIFLESSO AP D62 NERO   |
| <b>Installazione</b> | Lampade da parete      |
| <b>Garanzia</b>      | 5 years                |
| <b>Peso lordo</b>    | 1.17 kg                |
| <b>Volume</b>        | 0.00387 m <sup>3</sup> |

## Info tecniche e installative

|                                  |  |
|----------------------------------|--|
| <b>Peso netto</b>                | 0.85 kg  |
| <b>Classe di isolamento</b>      | I  |
| <b>Grado di protezione</b>       | IP44   |
| <b>Conformità</b>                | CE   |
| <b>Temperatura d'esercizio</b>   | 0° ~ +40 °C  |
| <b>Efficienza a pieno carico</b> | X  |
| <b>Dimmer</b>                    | NO, On-Off   |
| <b>Alimentazione</b>             | 220-240 V AC 50/60 Hz  |
| <b>Alimentatore</b>              | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

## Info sorgente e prestazionali

|                              |   |
|------------------------------|---|
| <b>Sorgente integrata</b>    | Integrated LED module                     |
| <b>Sorgente sostituibile</b> | Replaceable (by qualified operators only) |
| <b>Potenza</b>               | LED 17 W                                  |
| <b>Emissione</b>             | Diffuse                                   |
| <b>Consumo massimo</b>       | max 17,00 W                               |
| <b>Caratteristiche LED</b>   | LED SMD                                   |
| <b>CCT LED</b>               | 3000 K                                    |
| <b>Durata LED (t. 25°C)</b>  | 30000 h                                   |
| <b>CRI</b>                   | > 80                                      |
| <b>Flusso sorgente</b>       | 1800 lm                                   |
| <b>Flusso utile</b>          | 1020 lm                                   |
| <b>Rischio fotobiologico</b> | 1   |
| <b>Lampadina inclusa</b>     | 1 - E14 OLIVA 4W 3000K CRI80 SATIN        |

