
# Quark

rev. 25-01-2024




## General info

**Technical - Recessed lights**

| | |
|---|---|
| **Ean** | 8021696305844 |
| **Item** | QUARK FI 2.8W 3000K BK |
| **Installation** | Recessed lights |
| **Guarantee** | 5 years |
| **Gross weight** | 0.05 kg |
| **Volume** | 0.000413 $m^3$ |

## Technical info

| | |
|---|---|
| **Net weight** | 0.02 kg |
| **Insulation class** | II |
| **Protection index** | IP20 |
| **Compliance** | CE |
| **Operating temperature** | 0° ~ +40 °C |
| **Full load efficiency** | x |
| **Dimmer** | NO, On-Off |
| **Power output** | 220-240 V AC 50/60 Hz |
| **Power supply** | Separate, included<br>Replaceable (by qualified operators only), electronic |
| **Recessed specifications** | Ø 18 - h. ≥ 40 , 5-25 |

## Source info

| | |
|---|---|
| **Integrated source** | Integrated LED module |
| **Repleaceable source** | No |
| **Power** | 2,8 W |
| **Emission** | Direct |
| **Max consuption** | max 2,80 W |
| **Features LED** | LED SMD BRIDGELUX |
| **CCT LED** | 3000 K |
| **Duration LED (t. 25°c)** | 30000 h |
| **CRI** | > 90 |
| **Light beam** | 30° |
| **Light beam flux** | 180 lm |
| **Useful light flux** | 80 lm |
| **Photobiological risk** | 2 |

**IDEAL LUX s.r.l.**
Via Taglio Destro, 32, 30035 Mirano (Venezia)
**Tel** +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com