



Info generali

Tecnico - Sistemi

Indoor track mounted adjustable and dimmable projector with integrated LED sources and direct light emission

Ean	8021696329505
Articolo	STICK TRACK SINGLE 03W
Installazione	Sistemi
Garanzia	5 years
Peso lordo	0.11 kg
Volume	0.000593 m ³

Info tecniche e installative

Peso netto	0.07 kg
Classe di isolamento	III
Grado di protezione	IP20
Conformità	CE
Temperatura d'esercizio	0° ~ +40 °C
Efficienza a pieno carico	x
Dimmer	1, Phase-cut
Alimentazione	48 V DC
Alimentatore	Required, remoted, not included Replaceable (by qualified operators only)
Accessori non inclusi	Stick profile

Info sorgente e prestazionali

Sorgente integrata	Integrated LED module
Sorgente sostituibile	Replaceable (by qualified operators only)
Potenza	3 W
Emissione	Direct
Consumo massimo	max 3,00 W
Caratteristiche LED	LED COB BRIDGELUX
CCT LED	3000 K
Durata LED (t. 25°c)	30000 h
CRI	> 90
Fascio luminoso	24°
Flusso sorgente	270 lm
Flusso utile	190 lm
Rischio fotobiologico	1
Potenza in stand-by	< 0.50 W