

OPTYKA
OPTICS

AS



ASW



ASP



S

METAL KOLOR
METAL COLORszary 7043
grey 7043grafitowy 7016
graphite 7016czarny 9005
black 9005

RAL

na zamówienie
on request

index		wymiany/dimensions [cm]		źródło światła/source of light			oprawa/fixture			fundament foundation
		H/h ₁	w/S/s ₁	W	lm	lm/W	W	lm	lm/W	
191-1111-000023	GEDANUS K	120/-	375/-/-	31,5	4850	154	36	3240	90	-
190-1111-351002	GEDANUS PR LP 3,5	375/350	-/12x12/7x7	31,5	4850	154	36	3240	90	FBO 80/14,5
190-1111-352002	GEDANUS LP 3,5/2	375/350	110/12x12/7x7	63	9600	154	72	6440	90	FBO 80/14,5
190-1111-353003	GEDANUS LP 3,5/3	375/350	130/12x12/7x7	94,5	9600	154	108	9720	90	FBO 80/14,5
190-1111-420003	GEDANUS LP 4/2	425/400	110/12x12/7x7	63	9600	154	72	6440	90	FBO 80/14,5
190-1111-430001	GEDANUS LP 4/3	425/400	130/12x12/7x7	94,5	14250	154	108	9720	90	FBO 80/14,5

H – wysokość całkowita / total height h₁ – wysokość źródła światła / light source height w – wysięg / arm boomS – przekrój I stopnia u podstawy / 1st stage cross section in the base s₁ – przekrój II stopnia / 2nd stage cross section

Przybliżone dane w tabelach na 2022 rok. Dokładne dane dostępne w specyfikacjach. / Approximated data for 2022 in tables. Exact data available in specifications.

GEDANUS

by ELMARCO

GEDANUS

Klasyczna latarnia zbudowana z aluminiowej konstrukcji. Kolumnę stanowi kwadratowy profil z dekoracjami, na której osadzona jest oprawa lub system ramion 2 lub 3 płomiennych z elementem dekoracyjnym.

Proponowana oprawa: Gedania 36 W LED

Przeznaczenie: oświetlenie przestrzeni o historycznym, sakralnym charakterze, jak również parków, skwerów, uliczek.

Classic lantern made of an aluminum construction. Its column is formed by a square profile with décors on which a frame or a 2- or 3-lighting arm system with a decorative element is mounted.

Suggested fixture: Gedania 36 W LED

Designed for: illumination of historical, sacred sites as well as parks, squares, streets.

Proponowana oprawa
Suggested fixture

GEDANIA



STANDARD

IP 65	CLASS I/II	CE		ENERGY D	IK 08	4000°K 700 mA	CRI ≥ 70 ≥ 80
złącze IP 55 connection box IP 55	do wyboru optional				szkło IK 07 glass IK 07		do wyboru optional

NA ZAMÓWIENIE / ON REQUEST

	2700°K - 5000°K	300 mA - 1050 mA	10 kV
--	-------------------------------------	--------------------------------------	--------------



przykład / example