







BELL M




BELL S



BELL 72



BELL 48



BELL 32

OPTYKA
OPTICS

AS



ASW



ASP



S

METAL KOLOR
METAL COLORbiały 9003
white 9003szary 7043
grey 7043grafitowy 7016
graphite 7016czarny 9005
black 9005na zamówienie
on request

RAL

index		wymiany/dimensions			źródło światła/source of light			oprawa/fixture			wiatr/wind		masa/weight
		L/B/H [cm]			W	lm	lm/W	W	lm	lm/W	m ²	kg	
195-1111-000073	BELL S 32	56/56/51	32	4900	154	36	4000	112	0,12	6			
195-1111-000078	BELL M 32	56/56/44	32	4900	154	36	3450	96	0,12	6			
195-1111-000074	BELL S 2 x 24 AS	56/56/51	48	7400	154	55	6150	112	0,12	6			
195-1111-000079	BELL M 2 x 24 AS	56/56/44	48	7400	154	55	5300	96	0,12	6			
195-1111-000077	BELL S 3 x 24 AS	56/56/51	72	11100	154	83	9300	112	0,12	6,5			
195-1111-000082	BELL M 3 x 24 AS	56/56/44	72	11100	154	83	8000	96	0,12	6,5			

L — długość / lenght B — szerokość / width H — wysokość / height

Przybliżone dane w tabelach na 2022 rok. Dokładne dane dostępne w specyfikacjach.
Approximated data for 2022 in tables. Exact data available in specifications.

BELL

by ELMARCO

BELL

Klasyczna oprawa przystosowana do montażu do wysięgnika (ø60 mm) na wysokości 4–7 m. Aluminiowy korpus stanowi szczelną komorę, zamkniętą płytą, na której od strony klasza zamontowano moduł LED z soczewkami, a od wewnątrz radiator i zasilacz. Komora połączona jest z górną rozetą, która stanowi oprócz dekoracyjnej funkcji uchwyt montażowy.

Klosz z poliwęglanu odpornego na UV. Źródło światła: panel LED z systemem soczewek i odbłyśnika formujący wymaganą bryłę światła. Moduł zasilający: zestaw złączy oraz energooszczędny zasilacz przystosowany do sterowania.

Przeznaczenie: oświetlenie dróg, ulic, placów. Dzięki uniwersalnej formie pasuje do stylowego i nowoczesnego otoczenia.

Classic fixture adapted to be mounted on a boom (ø60 mm) at a height of 4–7 m. Aluminum body forms a sealed chamber (closed with a plate) with a sealed LED module (with the lens) mounted from the lamp-shade's side and a heat-sink and power supply unit — from the inside. The chamber is connected to the upper rosette, which — apart from its decorative function, also serves as a mounting bracket.

Lamp-shade made of polycarbonate being resistant to UV radiation. Light source: LED panel with a system of lenses and reflector forming any required shape of light. Power module: a set of quick couplings and energy-saving power supply unit designed for power control.

Designed for: illumination of roads, streets, squares. Thanks to its universal construction it fits to all types of stylish and modern surroundings.

STANDARD

IP 65	CLASS I/II	CE	RECYCLE	ENERGY D	IK 08	4000°K 700 mA	CRI ≥70 ≥80
złącze IP 55 connection box IP 55	do wyboru optional				szkło IK 07 glass IK 07		do wyboru optional

NA ZAMÓWIENIE / ON REQUEST

DIM	2700°K – 5000°K	300 mA – 1050 mA	10 kV
------------	--------------------------------	---------------------------------	--------------



przykład / example