

# SABA

SMALL SIZE



E27 hexagonal lantern in classic style, made of shockproof resin material, UV-rays stabilized, rust and corrosion-free. Modular construction suitable for post top, hanging and wall installation. Supplied as optional with TÜV-CB certified, long-life and efficient **LED lamps** suitable for outdoor use. Insulation class II, protection rating IP55.

*Lanterna esagonale E27 in stile classico, realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Idonea per il montaggio a palo, a sospensione o a parete. Fornita anche completa di lampadine LED adatte ad uso in ambiente esterno, certificate TÜV-CB, di lunga durata ed elevata efficienza. Classe di isolamento II, grado di protezione IP55.*

6,5W 800 lm	8,5W 920 lm	11W 1200 lm
2700 K	2700 K	4000 K 6500 K
+80°C -30°	90% HUMIDITY	VOLTAGE SURGE RESISTANT

**INDOOR & OUTDOOR USE**



K22.131.V1K






**SABA - LANTERN COMPONENTS**

**IP55**



Decorative **PINNACLE** to be mounted on the roof top for post installation or on the lantern base for hanging installation.

**PINNACOLO** decorativo applicabile alla sommità del tetto (montaggio a palo) o sulla base della gabbia (montaggio a sospensione).

Lantern **ROOF** made of shockproof resin material, UV rays stabilized and supplied with E27 lampholder. Tool-free opening for relamping and maintenance.

**TETTO** realizzato in resina antiurto, stabilizzata ai raggi UV, fornito completo di portalamпада E27. Rimovibile senza l'ausilio di attrezzi per manutenzione e cambio lampadina.

**DIFFUSER** made of UV stabilized polymethylmethacrylate (PMMA) resistant to yellowing process due to sun rays, available in clear or opal color and provided with recess for power cable supply. Made of one piece only and closed at the bottom to ensure high protection against external agents (IP 55).

**DIFFUSORE** in polimetilmetacrilato (PMMA) resistente al processo di ingiallimento dovuto ai raggi solari, disponibile in colore trasparente od opale e provvisto di scanalatura per il passaggio del cavo di alimentazione. Realizzato in un pezzo unico e con fondo chiuso per garantire un alto livello di protezione contro gli agenti esterni (IP 55).

**CAGE** made of shockproof resin material, UV-rays stabilized, rust and corrosion-free.

**GABBIA** realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione.

**SABA**

K22.000 \*



**Dimensions and weight**

Height: 320 mm  
Width: 220 mm  
Depth: 192 mm  
Weight: 1 Kg

**Moulded colours:**

Black  White

**Painted colours:**

Antique green  Antique bronze

**Diffuser PMMA:**

Clear  Opal

**E27 FILAMENT**



- Perfect **MATCHING WITH DECORATIVE LANTERNS.**
- **SUITABLE FOR OUTDOOR USE:** 100-240V driver.
- **360°OMNIDIRECTIONAL LIGHT.**
- **HIGH EFFICIENCY:** 90% ENERGY SAVING.

**E27 CCT SET(\*)**



- **A60 CCT SETTABLE:** 2700K/4000K/6500K.
- **SUITABLE FOR OUTDOOR USE:** 100-240V driver.
- **EYE COMFORT** opal glass.
- **HIGH EFFICIENCY:** >85% ENERGY SAVING.

**100 - 240 V**

\*ADD SUFFIX


suitable lamps: CFL-LED max 160 mm		<b>E27</b> lampholder only		.E27
LAMP	POWER	LUMINOUS FLUX UP TO	COLOUR TEMP.	
FILAMENT LED E27	6,5W	800 lm	2700 K	.F1R
CCT SET LED E27	8,5 W	920 lm	6500 K	.V1K
			4000 K	
			2700 K	

6,5W filament = 60W incandescent

8,5W CCT


**SAVE up to 89%**

**LED LAMPS**





Comply with: EU2019/2015  
EU2019/2020  
Technical details on page 636.

**CCT SETTABLE LED LAMP(\*)**



**PHOTOMETRIC DATA SAMPLE**



**SABA lantern clear with Fumagalli Filament Led Lamp 6,5W.**

POST height 1mt  
6x6mt area: average 6 lux

The photometric data for all the versions are available upon request or on our website.

CCT switch settable in three different positions, to select the desired Kelvin temperature (2700K/4000K/6500K) and get a customized ambience.

\* ADD THESE SUFFIXES TO THE REFERENCES MENTIONED IN THE CATALOGUE

# SABA

SMALL SIZE



K22.156.S20.V1K



K22.156.S30.F1R



K22.156.S20.F1R





**ARTU' BISSO/SABA 2+1**

<b>E27</b> lampholder	K22.158.S21.E27
<b>6,5W</b> filament	K22.158.S21.F1R
<b>8,5W</b> CCT set	K22.158.S21.V1K

Pcs 1  
Kg 12,1  
mc 0,176

**ARTU' BISSO/SABA 3+1**

<b>E27</b> lampholder	K22.158.S31.E27
<b>6,5W</b> filament	K22.158.S31.F1R
<b>8,5W</b> CCT set	K22.158.S31.V1K

Pcs 1  
Kg 13,1  
mc 0,176

**GIGI BISSO/SABA 2+1**

<b>E27</b> lampholder	K22.156.S21.E27
<b>6,5W</b> filament	K22.156.S21.F1R
<b>8,5W</b> CCT set	K22.156.S21.V1K

Pcs 1  
Kg 14,1  
mc 0,182

**GIGI BISSO/SABA 3+1**

<b>E27</b> lampholder	K22.156.S31.E27
<b>6,5W</b> filament	K22.156.S31.F1R
<b>8,5W</b> CCT set	K22.156.S31.V1K

Pcs 1  
Kg 15,1  
mc 0,182

**ARTU' BISSO/SABA 2L**

<b>E27</b> lampholder	K22.158.S20.E27
<b>6,5W</b> filament	K22.158.S20.F1R
<b>8,5W</b> CCT set	K22.158.S20.V1K

Pcs 1  
Kg 11,1  
mc 0,176

**ARTU' BISSO/SABA 3L**

<b>E27</b> lampholder	K22.158.S30.E27
<b>6,5W</b> filament	K22.158.S30.F1R
<b>8,5W</b> CCT set	K22.158.S30.V1K

Pcs 1  
Kg 12,1  
mc 0,176

**GIGI BISSO/SABA 2L**

<b>E27</b> lampholder	K22.156.S20.E27
<b>6,5W</b> filament	K22.156.S20.F1R
<b>8,5W</b> CCT set	K22.156.S20.V1K

Pcs 1  
Kg 13,1  
mc 0,182

**GIGI BISSO/SABA 3L**

<b>E27</b> lampholder	K22.156.S30.E27
<b>6,5W</b> filament	K22.156.S30.F1R
<b>8,5W</b> CCT set	K22.156.S30.V1K

Pcs 1  
Kg 14,1  
mc 0,182