

GARDEN REVIVAL
GARDEN CLASSIC
BOLLARD
UP&DOWN
DOWNLIGHT
IN-GROUND
BRICKLIGHT
FLOODLIGHT
BULKHEAD
SOLAR
URBAN CLASSIC
URBAN REVIVAL
URBAN MODERN
POST
LAMPS

SALEM

MEDIUM SIZE



E27 hexagonal lantern in classic style, made of shockproof resin material, UV-rays stabilized, rust and corrosion-free. Modular construction suitable for post top, hanging and wall installation. Supplied as optional with TÜV-CB certified, long-life and efficient **LED lamps** suitable for outdoor use. Insulation class II, protection rating IP55.

*Lanterna esagonale E27 in stile classico, realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Idonea per il montaggio a palo, a sospensione o a parete. Fornita anche completa di **lampadine LED** adatte ad uso in ambiente esterno, certificate TÜV-CB, di lunga durata ed elevata efficienza. Classe di isolamento II, grado di protezione IP55.*

6,5W 800 lm	8,5W 920 lm	11W 1200 lm	
2700 K	2700 K	4000 K	6500 K
+80°C -30°	90% HUMIDITY	VOLTAGE SURGE RESISTANT	
INDOOR & OUTDOOR USE			



K26.111.F1R





SALEM - LANTERN COMPONENTS

IP55

Decorative **PINNACLE** to be mounted on the roof top for post installation or on the lantern base for hanging installation.

***PINNACOLO** decorativo applicabile alla sommità del tetto (montaggio a palo) o sulla base della gabbia (montaggio a sospensione).*

Lantern **ROOF** made of shockproof resin material, UV rays stabilized and supplied with E27 lampholder. Tool-free opening for relamping and maintenance.

***TETTO** realizzato in resina antiurto, stabilizzata ai raggi UV, fornito completo di portalamпада E27. Rimovibile senza l'ausilio di attrezzi per manutenzione e cambio lampadina.*

DIFFUSER made of UV stabilized polymethylmethacrylate (PMMA) resistant to yellowing process due to sun rays, available in clear or opal color and provided with recess for power cable supply. Made of one piece only and closed at the bottom to ensure high protection against external agents (IP 55).

***DIFFUSORE** in polimetilmetacrilato (PMMA) resistente al processo di ingiallimento dovuto ai raggi solari, disponibile in colore trasparente od opale e provvisto di scanalatura per il passaggio del cavo di alimentazione. Realizzato in un pezzo unico e con fondo chiuso per garantire un alto livello di protezione contro gli agenti esterni (IP 55).*

CAGE made of shockproof resin material, UV-rays stabilized, rust and corrosion-free.

***GABBIA** realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione.*



Dimensions and weight

Height: 410 mm
Width: 260 mm
Depth: 227 mm
Weight: 1,3 Kg

Moulded colours:

Black White

Painted colours:

Antique green Antique bronze

Diffuser PMMA:

Clear Opal

E27 FILAMENT	E27 CCT SET(*)	100 - 240 V	*ADD. SUFFIX																				
		<p>suitable lamps: CFL-LED max 160 mm</p> <p>E27 lampholder only .E27</p> <table border="1"> <thead> <tr> <th>LAMP</th> <th>POWER</th> <th>LUMINOUS FLUX UP TO</th> <th>COLOUR TEMP.</th> <th></th> </tr> </thead> <tbody> <tr> <td></td> <td>6,5W</td> <td>800 lm</td> <td>2700 K</td> <td>.F1R</td> </tr> <tr> <td></td> <td>8,5 W</td> <td>920 lm</td> <td>6500 K 4000 K 2700 K</td> <td>.V1K</td> </tr> <tr> <td></td> <td>11 W</td> <td>1200 lm</td> <td>6500 K 4000 K 2700 K</td> <td>.T1K</td> </tr> </tbody> </table>	LAMP	POWER	LUMINOUS FLUX UP TO	COLOUR TEMP.			6,5W	800 lm	2700 K	.F1R		8,5 W	920 lm	6500 K 4000 K 2700 K	.V1K		11 W	1200 lm	6500 K 4000 K 2700 K	.T1K	
LAMP	POWER	LUMINOUS FLUX UP TO	COLOUR TEMP.																				
	6,5W	800 lm	2700 K	.F1R																			
	8,5 W	920 lm	6500 K 4000 K 2700 K	.V1K																			
	11 W	1200 lm	6500 K 4000 K 2700 K	.T1K																			
<ul style="list-style-type: none"> perfect MATCHING WITH DECORATIVE LANTERNS. SUITABLE FOR OUTDOOR USE: 100-240V driver. 360°OMNIDIRECTIONAL LIGHT. HIGH EFFICIENCY: 90% ENERGY SAVING. 	<ul style="list-style-type: none"> A60 CCT SETTABLE: 2700K/4000K/6500K. SUITABLE FOR OUTDOOR USE: 100-240V driver. EYE COMFORT opal glass. HIGH EFFICIENCY: >85% ENERGY SAVING. 	<p>6,5W filament = 60W incandescent</p> <p>8,5W CCT = 75W incandescent</p> <p>11W CCT = 75W incandescent</p> <p>SAVE up to 89%</p>																					

LED LAMPS

LVD EMC ERP

Comply with: EU2019/2015
EU2019/2020
Technical details on page 636.

CCT SETTABLE LED LAMP(*)

PHOTOMETRIC DATA SAMPLE

SALEM lantern clear with Fumagalli Led Lamp CCT set 8,5W.

POST height 2mt
6x6mt area: average 6 lux

The photometric data for all the versions are available upon request or on our website.

CCT switch settable in three different positions, to select the desired Kelvin temperature (2700K/4000K/6500K) and get a customized ambience.

* ADD THESE SUFFIXES TO THE REFERENCES MENTIONED IN THE CATALOGUE

SALEM

MEDIUM SIZE



MADE IN ITALY



BISSO/SALEM	
E27 lampholder	K26.131.E27
6,5W filament	K26.131.F1R
8,5W CCT set	K26.131.V1K
11W CCT set	K26.131.T1K
Pcs 12 Kg 19 mc 0,225	

SICHEM/SALEM	
E27 lampholder	K26.120.E27
6,5W filament	K26.120.F1R
8,5W CCT set	K26.120.V1K
11W CCT set	K26.120.T1K
Pcs 12 Kg 19 mc 0,225	

SALEM	
K26.000	
Pcs 1 Kg 1,3 mc 0,018	

MINILOT/SALEM	
E27 lampholder	K26.111.E27
6,5W filament	K26.111.F1R
8,5W CCT set	K26.111.V1K
11W CCT set	K26.111.T1K
Pcs 12 Kg 19 mc 0,225	

PORPORA/SALEM	
E27 lampholder	K26.141.E27
6,5W filament	K26.141.F1R
8,5W CCT set	K26.141.V1K
11W CCT set	K26.141.T1K
Pcs 1 Kg 4 mc 0,034	

IAFET/SALEM resin	
E27 lampholder	K26.162.E27
6,5W filament	K26.162.F1R
8,5W CCT set	K26.162.V1K
11W CCT set	K26.162.T1K
Pcs 2 Kg 7,9 mc 0,086	

MIZAR/SALEM resin	
E27 lampholder	K26.151.E27
6,5W filament	K26.151.F1R
8,5W CCT set	K26.151.V1K
11W CCT set	K26.151.T1K
Pcs 1 Kg 3 mc 0,07	

ALOE'R/SALEM resin	
E27 lampholder	K26.163.E27
6,5W filament	K26.163.F1R
8,5W CCT set	K26.163.V1K
11W CCT set	K26.163.T1K
Pcs 2 Kg 8,6 mc 0,121	

ARTU'/SALEM	
E27 lampholder	K26.158.E27
6,5W filament	K26.158.F1R
8,5W CCT set	K26.158.V1K
11W CCT set	K26.158.T1K
Pcs 1 Kg 9,6 mc 0,148	