

GARDEN REVIVAL
GARDEN CLASSIC
BOLLARD
UP&DOWN
DOWNLIGHT
IN-GROUND
BRICKLIGHT
FLOODLIGHT
BULKHEAD
SOLAR
URBAN CLASSIC
URBAN REVIVAL
URBAN MODERN
POST
LAMPS

STEVEN

BOLLARD



LED bollard with modern design and directed light emission, made of shockproof resin material, UV-rays stabilized, rust and corrosion-free. Dual use: suitable both for spike and ground installation. Supplied with TÜV-CB certified, long-life and efficient **G9 LED lamp included**. Insulation class II, protection rating IP67.

*Bollard a led in stile moderno con emissione della luce direzionata, realizzato in resina antiurto, stabilizzato ai raggi UV, inattaccabile da ruggine e corrosione. Doppia modalità di installazione al suolo, con picchetto o tasselli. Fornito con **inclusa lampadina a LED G9**, certificata TUV-CB di lunga durata ed elevata efficienza. Classe di isolamento II, grado di protezione IP67.*



ST1.531.Z1R

RECYCLABLE	ANTI-SHOCK	TEMPERATURE		POST	

MADE IN ITALY

STEVEN - COMPONENTS

IP67



GROUND
INSTALLATION

SPIKE
INSTALLATION

HOUSING made in shockproof resin material. Provided with G9 lampholder and watertight cable gland for a safe electrical devices connection.

CASSA realizzata in resina antiurto. Provvista di portalampana G9 e pressacavo a tenuta stagna, per consentire una sicura connessione degli accessori elettrici.

DIFFUSER made of shockproof resin material (PC) complete with silicone rubber gasket to ensure high protection against external agents. Frosted or coloured versions, to get a customized ambiance.

DIFFUSORE in resina antiurto (PC) completo di guarnizione in gomma siliconica per garantire un alto livello di protezione contro gli agenti esterni. Disponibile nella versione satinata o colorata, per ottenere un'ambientazione personalizzata.



COVER with no visible screws made in shockproof resin material.

COVER senza viti a vista realizzata in resina antiurto.

POLE in one piece only complete with spike. Made in shockproof resin material, UV rays stabilized, rust and corrosion free. Dual use: you can fix the spike outside the pole for in-ground installation, or inside the pole for surface installation with screws.

PALO in un unico pezzo completo di picchetto. Fabbricato in resina antiurto stabilizzato ai raggi UV, inattaccabile da ruggine e corrosione. Duplice utilizzo: il picchetto può essere montato all'esterno del palo per installazione diretta nel terreno o al suo interno per installazione al suolo mediante tasselli di fissaggio.

DUAL
USE

STEVEN



Dimensions and weight

Diameter: 50 mm
Height: 450 mm
Weight: 0,65 Kg

Cover colours:

Black White Grey

Diffuser PC:

Frosted
Blue Green Orange

G9 LED

100 - 240 V



Bollard supplied as standard with TÜV-CB certified, long-life and efficient **G9 LED lamp included**. Quick and easy lamp replacement for a very simple maintenance after installation.

- **COST SAVING:** long-life and efficient LED light sources.
- **BUILT-IN DRIVER:** quick and easy lamp replacement.
- **GREAT FLEXIBILITY:** G9 standard lamp holder.
- **FUTURE-PROOFED LUMINARIES:** performances easy to upgrade to latest technology developments.
- **100-240V:** wide voltage range to protect the driver from power surges.

LAMP	POWER	LUMINOUS FLUX UP TO	COLOUR TEMP.	*ADD. SUFFIX
	1,7 W	150 lm	4000 K	.Z1L
			3000 K	.Z1R

LED LAMPS




Comply with: EU2019/2015
EU2019/2020
Technical details on page 636.

* ADD THESE SUFFIXES TO THE REFERENCES
MENTIONED IN THE CATALOGUE

STEVEN

BOLLARD





STEVEN		
ST1.531.Z1L	1,7W	ST1.531.Z1R
4000K	G9 LED LAMP INCLUDED	3000K
SPIKE INSTALLATION GROUND INSTALLATION DUAL USE		
Pcs 10 Kg 8,5 mc 0,092		