

# DARIO

MEDIUM SIZE



E27 square lantern in modern revival style, made of shockproof resin material, UV-rays stabilized, rust and corrosion-free. Modular construction suitable for post top, hanging and wall installation. Supplied as optional with TÜV-CB certified, long-life and efficient **LED lamps** suitable for outdoor use. Insulation class II, protection rating IP55.

*Lanterna quadra E27 in stile revival moderno, realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Idonea per il montaggio a palo, a sospensione o a parete. Fornita anche completa di lampadine LED adatte ad uso in ambiente esterno, certificate TÜV-CB, di lunga durata ed elevata efficienza. Classe di isolamento II, grado di protezione IP55.*

|                      |                |                         |
|----------------------|----------------|-------------------------|
|                      |                |                         |
| 6,5W<br>800 lm       | 8,5W<br>920 lm | 11W<br>1200 lm          |
| 2700 K               | 2700 K         | 4000 K 6500 K           |
| +80°C<br>-30°        | 90% HUMIDITY   | VOLTAGE SURGE RESISTANT |
| INDOOR & OUTDOOR USE |                |                         |



T24.116.V1K

|  |  |  |  |
|--|--|--|--|
|  |  |  |  |
|  |  |  |  |
|  |  |  |  |
|  |  |  |  |



ROBY

DARIO

SERGIO

### DARIO - LANTERN COMPONENTS

IP55



Decorative **PINNACLE** provided with silicone rubber gasket to be mounted on the roof top for post installation or on the lantern base for hanging installation.

**PINNACOLO** decorativo completo di guarnizione in gomma silconica applicabile alla sommità del tetto (montaggio a palo) o sulla base della gabbia (montaggio a sospensione).

Lantern **ROOF** made of shockproof resin material, UV rays stabilized and supplied with E27 lampholder. Tool-free opening for relamping and maintenance.

**TETTO** realizzato in resina antiurto, stabilizzata ai raggi UV, fornito completo di portalamпада E27. Rimovibile senza l'ausilio di attrezzi per manutenzione e cambio lampadina.

**DIFFUSER** made of UV stabilized polymethylmethacrylate (PMMA) resistant to yellowing process due to sun rays, available in clear or opal color and provided with recess for power cable supply. Made of one piece only and closed at the bottom to ensure high protection against external agents (IP 55).

**DIFFUSORE** in polimetilmetacrilato (PMMA) resistente al processo di ingiallimento dovuto ai raggi solari, disponibile in colore trasparente od opale e provvisto di scanalatura per il passaggio del cavo di alimentazione. Realizzato in un pezzo unico e con fondo chiuso per garantire un alto livello di protezione contro gli agenti esterni (IP 55).

**CAGE** made of shockproof resin material, UV-rays stabilized, rust and corrosion-free.

**GABBIA** realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione.

### DARIO

T24.000 \*



#### Dimensions and weight

Height: 240 mm

Width: 240 mm

Depth: 240 mm

Weight: 1,1 Kg

#### Moulded colours:

Black White

Grey

#### Diffuser PMMA:

Clear Opal

### E27 FILAMENT



- perfect **MATCHING WITH DECORATIVE LANTERNS.**
- **SUITABLE FOR OUTDOOR USE:** 100-240V driver.
- **360°OMNIDIRECTIONAL LIGHT.**
- **HIGH EFFICIENCY:** 90% ENERGY SAVING.

### E27 CCT SET(\*)



- **A60 CCT SETTABLE:** 2700K/4000K/6500K.
- **SUITABLE FOR OUTDOOR USE:** 100-240V driver.
- **EYE COMFORT** opal glass.
- **HIGH EFFICIENCY:** >85% ENERGY SAVING.

### 100 - 240 V

\*ADD. SUFFIX

| suitable lamps:<br>CFL-LED<br>max 160 mm                                                                   |       | E27<br>lampholder only |                 | .E27 |
|------------------------------------------------------------------------------------------------------------|-------|------------------------|-----------------|------|
| LAMP                                                                                                       | POWER | LUMINOUS<br>FLUX UP TO | COLOUR<br>TEMP. |      |
| <br>FILAMENT<br>LED E27 | 6,5W  | 800 lm                 | 2700 K          | .F1R |
| <br>CCT SET<br>LED E27  | 8,5 W | 920 lm                 | 6500 K          | .V1K |
|                                                                                                            |       |                        | 4000 K          |      |
|                                                                                                            |       |                        | 2700 K          |      |

  
6,5W  
filament

=

60W  
incandescent



  
8,5W  
CCT


**SAVE up to 89%**

### LED LAMPS





Comply with: EU2019/2015  
EU2019/2020  
Technical details on page 636.

### CCT SETTABLE LED LAMP(\*)



CCT switch settable in three different positions, to select the desired Kelvin temperature (2700K/4000K/6500K) and get a customized ambience.

### PHOTOMETRIC DATA SAMPLE



**DARIO** lantern clear with  
Fumagalli Led Lamp CCT set 8,5W.

POST height 2mt  
6x6mt area: average 6 lux

The photometric data for all the versions are available upon request or on our website.

\* ADD THESE SUFFIXES TO THE REFERENCES MENTIONED IN THE CATALOGUE

# DARIO

MEDIUM SIZE





ROBY



DARIO



SERGIO

| DINO NARDO/DARIO 2L   |                 |
|-----------------------|-----------------|
| <b>E27</b> lampholder | T24.306.D20.E27 |
| <b>6,5W</b> filament  | T24.306.D20.F1R |
| <b>8,5W</b> CCT set   | T24.306.D20.V1K |

Pcs 1  
Kg 11,9  
mc 0,186

630

1960

2

Ø 245

| DINO NARDO/DARIO 3L   |                 |
|-----------------------|-----------------|
| <b>E27</b> lampholder | T24.306.D30.E27 |
| <b>6,5W</b> filament  | T24.306.D30.F1R |
| <b>8,5W</b> CCT set   | T24.306.D30.V1K |

Pcs 1  
Kg 12,9  
mc 0,186

620

1960

3

Ø 245

| EMILIO NARDO/DARIO 1L |                 |
|-----------------------|-----------------|
| <b>E27</b> lampholder | T24.307.D10.E27 |
| <b>6,5W</b> filament  | T24.307.D10.F1R |
| <b>8,5W</b> CCT set   | T24.307.D10.V1K |

Pcs 1  
Kg 11,4  
mc 0,212

370

2020

1

Ø 245

| EMILIO NARDO/DARIO 2L |                 |
|-----------------------|-----------------|
| <b>E27</b> lampholder | T24.307.D20.E27 |
| <b>6,5W</b> filament  | T24.307.D20.F1R |
| <b>8,5W</b> CCT set   | T24.307.D20.V1K |

Pcs 1  
Kg 12,5  
mc 0,212

630

2200

2

Ø 245

| EMILIO NARDO/DARIO 3L |                 |
|-----------------------|-----------------|
| <b>E27</b> lampholder | T24.307.D30.E27 |
| <b>6,5W</b> filament  | T24.307.D30.F1R |
| <b>8,5W</b> CCT set   | T24.307.D30.V1K |

Pcs 1  
Kg 13,5  
mc 0,212

620

2200

3

Ø 245