

Corpuri de iluminat stradal VISION



Cod	-	Watt	Lens	Lumeni	Kelvin	P.F.	Buc/Bax	Diametru Brat	Dimensiuni
VS-LS.P30.3		30W	-	3500	3000	>0.95	6	Φ60mm	400x170x95mm
VS-LS.P30.6		30W	-	3500	6500	>0.95	6	Φ60mm	400x170x95mm
VS-LS.P50.3		50W	-	6000	3000	>0.95	6	Φ60mm	400x170x95mm
VS-LS.P50.6		50W	-	6000	6500	>0.95	6	Φ60mm	400x170x95mm
VS-LS.P100.3		100W	-	12000	3000	>0.95	6	Φ60mm	400x170x95mm
VS-LS.P100.6		100W	-	12000	6500	>0.95	6	Φ60mm	400x170x95mm



Cod	-	Watt	Lens	Lumeni	Kelvin	P.F.	Buc/Bax	Diametru Brat	Dimensiuni
VS-LS.P150.6.L		150W	140°/ 70°	18.000	6500	>0.95	1	Φ60mm	500x240x95mm
VS-LS.P200.6.L		200W	140°/ 70°	24.000	6500	>0.95	1	Φ60mm	500x240x95mm



LED



85-265V



30000h



x30000



70°/135°



Non Dimmable



08



0.00%



-40/+60°C



IP65



Ra>80